

DECLARATION OF PERFORMANCE

N. 524-CPR-16-10

1. Unique identification code of the product-type: **RM200**
2. Intended uses: **Coloured rendering mortar (CR)**
3. Manufacturer: **FASSA S.r.l. – Via Lazzaris, 3 – 31027 Spresiano (TV) – ITALY –
www.fassabortolo.com**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 998-1: 2010**

Notified bodies: NA

7. Declared performances:

Reaction to fire	A1
Water absorption	W1
Water permeability after weathering cycles	NPD
Water vapor permeability	14
Adhesion	≥ 0,3 N/mm² - FP:B

Adhesion after weathering cycles	NPD
Thermal conductivity λ	0,53 W/mK (tabulated value)
Durability	NPD
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dott. Samuele Beraldo

Research & Development and Quality Direction – Inorganic Products Manager

Spresiano (TV), 03/10/2016

FASSA S.r.l.
Via Lazzaris n° 3
31027 SPRESIANO (TV)
Partita IVA 03015890268



FASSA S.r.l.

ETICHETTA CE

Prodotto: RM200



Fassa s.r.l.

Via Lazzaris, 3

31027 Spresiano (TV) – Italy

04

524-CPR-16-10

EN 998-1: 2010

RM200

Coloured rendering mortar (CR)

for external/internal use

Reaction to fire:	A1
Water absorption:	W1
Water permeability after weathering cycles:	NPD
Water vapour permeability:	14
Adhesion:	≥ 0,3 N/mm ² - FP:B
Adhesion after weathering cycles:	NPD
Thermal conductivity λ:	0,53 W/mK (tabulated value)
Durability:	NPD
Dangerous substances:	See MSDS